

IKA

designed for scientists

EN



POWERFUL STIRRING | Overhead Stirrers

Overhead Stirrers

/// Stirring at the highest level

IKA overhead stirrers are strong, sturdy and safe because we understand the most important aspects during development. From low to high viscosities, and with up to 200 liters of stirring volume, all mixing and stirring tasks constitute no challenge for our stirrers. This is a good foundation for differentiated functionalities, which include: a safety circuit, a clear display, convenient control using labworldsoft® laboratory software and a wide range of stirring tools. Whether it is propeller stirrers, anchor stirrers or spiral stirrers – you will find the right tool for all applications in our range.



Personalized application support

In the IKA Application Center you can test the overhead stirrers yourself. Our experts analyze your processes and work with you to find out how your application can be optimized.

Worldwide service

To opt for the IKA overhead stirrers is also to opt for the excellent IKA service in your region. Our team is available worldwide for your service and application needs. Availability of spare parts is guaranteed for 10 years.

Do you have any questions? Our service team is at your disposal:
00 8000 4524357 (00 8000 IKAHELP)

3 years warranty*

CE

*2+1 years after registering at www.ika.com/register, wearing parts excluded

Overhead Stirrers

/// Powerful stirring



NANO-, MICRO- and MINISTAR series

The space-saving high performers of the NANOSTAR, MICROSTAR and MINISTAR series convince with perfect basic functionalities, have a compact design and are easy-to-use.

EUROSTAR series

The EUROSTAR series offers indispensable features, which include: electronic safety circuit, short-term overload operation and monitoring of all parameters using labworldsoft® software.

RW series

The RW series is the robust and long established line in the market. This series comes with two gear settings to support high torque or high speed mixing respectively.



4
NANO-, MICRO- AND MINISTARS

32
TORQUE & SPEED

10
EUROSTARS

33
QUALITY STANDARDS

18
RW SERIES

34
KNOWLEDGE

20
ACCESSORIES

35
FAQ

NANO, MICRO- and MINISTARS

/// Compact and reliable

The space-saving high performers of the NANOSTAR, MICROSTAR and MINISTAR series convince with perfect basic functionalities, have a compact design and are easy-to-use.

Compact design

The reduced design and the focus on the most essential aspects make the NANOSTAR, MICROSTAR and MINISTAR stirrers reliable laboratory companions.



Constant torque

All models of the NANOSTAR, MICROSTAR and MINISTAR series guarantee a constant torque over the entire rpm range. The MICROSTAR and MINISTAR stirrers are available in six different versions with revolutions of up to 2000 rpm and a torque of up to 80 Ncm, each in a digital or control variant. The latest model NANOSTAR is available as 7.5 digital version.

Ease of operation

Operation takes place using a stable rotary knob. The display of the digital version clearly shows the rotational speed, while the display of the control version shows further information, such as medium temperature and torque. The integrated timer and counter function enables the monitoring of sensitive chemical reactions.



FEATURES

- › Fast response display covered with hardened glass for maximum visibility of parameters
- › Continuously adjustable speed
- › USB interface, e.g. for documenting parameters using labworldsoft® or installing firmware updates
- › High IP value 54 designed with chemical resistant housing and display
- › Microprocessor-controlled speed governor for constant rotational speed, even with changes in viscosity
- › R 300 shaft protector included to avoid accidental touching of moving chuck
- › Supports sample volume from low to high volume with different impeller designs

ADDITIONAL FEATURES

(control version only)

- › Clear display for all essential information: rpm, torque, temperature, timer/ counter
- › Touch-sensitive surface for long service life
- › State-of-the-art vibration sensors detect deviations from permissible thresholds and automatically stop the process
- › Timer and counter function
- › Display of the samples weight by connecting with the IKA [scale] plate stand via a wireless (WPAN) connection
- › Temperature sensor included for sample temperature measurement
- › Key lock function



Special safety precautions

The display of the stirrers is made of hardened and chemical-resistant glass. The stirrers' protection class IP54 ensures maximum safety. In addition, the state-of-the-art vibration sensors integrated in the control version detect deviations from permissible thresholds and automatically stop the process. The external, low-voltage power supply unit also contributes to increased safety.

Fast updates

Periodic software updates can be carried out quickly and easily via the USB interface. In addition, regulation via a PC and documentation of the test parameters is possible via the interface of the control devices.

NANOSTAR 7.5 digital
Ident. No. 0025004356

MICROSTAR 7.5 digital Ident. No. 0025004715	MICROSTAR 15 digital Ident. No. 0025004883	MICROSTAR 30 digital Ident. No. 0025004884
MICROSTAR 7.5 control Ident. No. 0025001984	MICROSTAR 15 control Ident. No. 0025001986	MICROSTAR 30 control Ident. No. 0025001987
MINISTAR 20 digital Ident. No. 0025004885	MINISTAR 40 digital Ident. No. 0025004886	MINISTAR 80 digital Ident. No. 0025004887
MINISTAR 20 control Ident. No. 0025001988	MINISTAR 40 control Ident. No. 0025001989	MINISTAR 80 control Ident. No. 0025001990

NANOSTAR



Original size

MICROSTARS



MINISTARS





Technical data

Technical data	NANOSTAR 7.5 digital
Stirring quantity max. (H ₂ O)	5 l
Speed	min.: 0/50 rpm max.: 2000 rpm
Viscosity max.	4000 mPas
Torque max. at stirring shaft	7.5 Ncm
Dimensions (W × H × D)	53 × 147 × 130 mm
Weight	0.8 kg

Technical data	MICROSTAR 7.5 digital control	MICROSTAR 15 digital control	MICROSTAR 30 digital control	MINISTAR 20 digital control	MINISTAR 40 digital control	MINISTAR 80 digital control
Stirring quantity max. (H ₂ O)	5 l	10 l	20 l	15 l	25 l	50 l
Speed	digital: 0/50 rpm control: 0/30 rpm max.: 2000 rpm	digital: 0/50 rpm control: 0/30 rpm max.: 1000 rpm	digital: 0/50 rpm control: 0/30 rpm max.: 500 rpm	min.: 0/50 rpm max.: 2000 rpm	digital: 0/50 rpm control: 0/30 rpm max.: 1000 rpm	digital: 0/50 rpm control: 0/30 rpm max.: 500 rpm
Viscosity max.	4000 mPas	8000 mPas	20 000 mPas	10 000 mPas	30 000 mPas	60 000 mPas
Torque max. at stirring shaft	7.5 Ncm	15 Ncm	30 Ncm	20 Ncm	40 Ncm	80 Ncm
Dimensions (W × H × D)	60 × 173 × 126 mm	60 × 173 × 126 mm	60 × 173 × 126 mm	70 × 193 × 147 mm	70 × 193 × 147 mm	70 × 193 × 147 mm
Weight	1.18 kg	1.26 kg	1.26 kg	1.56 kg	1.72 kg	1.72 kg



General data	NANO- MICRO- AND MINISTAR digital control
Speed display	LED LCD
Permissible ON time	100 %
Motor type	Brushless DC
Setting accuracy speed	± 1 rpm
Deviation of speed measurement n > 300 rpm	± 1 %
Deviation of speed measurement n < 300 rpm	± 3 rpm
Chuck range diameter	min. 0.5 mm max. 8.2 mm
Hollow shaft (push-through - when stopped)	Yes
Housing material	Alu-cast coating/ thermoplastic polymer
Protection class according to DIN EN 60529	IP 54
Interface	USB

EUROSTARS

/// The key to successful mixing

Designed to optimize complex stirring applications, IKA offers the very best in overhead stirrer technology. Our EUROSTAR series provides the perfect solution to all of your laboratory stirring and mixing needs, from lower to higher viscosities.

Twin Technology

The EUROSTAR 20 / 40 / 60 / 100 digital and EUROSTAR 60 / 100 control are redesigned with a new 23% smaller footprint and improved ergonomic and safety features. The new series offers an even higher torque capacity while also offering torque monitoring during processing. The RS232 and USB interface allow capability of external control and the new Quick Sense Keyless Chuck allows one hand operation.



FEATURES

EUROSTAR digital 20 / 40 / 60 / 100

- › 23% smaller size than previous models
- › Torque Trend Measurement
- › Quick Sense Keyless Chuck
- › Cleanroom ISO 7/8 Classification
- › IP 54
- › Timer/Counter function
- › Lock Key
- › LCD Display
- › USB Interface
- › RS 232

ADDITIONAL FEATURES


EUROSTAR control 60 / 100

- Additional features compared to digital version:
- › Viscosity measurement (mPas)
 - › High precision torque measurement +/- 1 Ncm
 - › Vibration sensor
 - › Integrated Light
 - › Left/Right rotation direction (interval mode)
 - › Speed: Soft start in 3 modes
 - › Chaotic Mixing Mode
 - › Lock ring indication (chuck)
 - › Temperature measurement
 - › Program mode
 - › Graph display
 - › TFT Display
 - › Wireless (WPAN), Ethernet & Wifi connection



New Torque Performance Model

IKAs previous EUROSTAR series torque principle used the IKA's motors name as the maximum torque the motor can provide. IKA's new EUROSTAR series nomenclature now represents the torque which is offered even at maximum rpm, with high torque capabilities in lower rpm range.



Measure viscosity and display it, even during product development
Unique Accurate Torque Sensor (+/- 1 Ncm accuracy) allows you to calculate viscosity (m*Pas) with IKA conditions or user-defined calibration. The result can be read in real-time on the TFT display.



The only two stirrers with **clockwise and counter clockwise rotation** for intensive applications and better mixing results.



FEATURES

EUROSTAR 100 digital

- › Laboratory stirrer designed for highly viscous applications and intensive mixing
- › Digital display for precise monitoring of set and actual speeds



FEATURES

EUROSTAR 100 control

- › Clockwise and counter clockwise rotation
- › TFT display for better image quality and easy navigation



FEATURES

EUROSTAR 400 high torque digital

- › Laboratory stirrer for high torque demand
- › Torque Max 400 Ncm
- › Viscosity Max 100,000 mPas



FEATURES

EUROSTAR 20 high speed digital | control

- › High-speed stirrer for intensive mixing
- › Extremely powerful laboratory stirrer designed for intensive stirring tasks
- › Options for propellers or dissolver impellers (accessories)
- › Fast dissolving / dispersing with mixing speed of up to 6000 rpm

New for control Model

- › Vibration sensor
- › Chaotic mixing



FEATURES

EUROSTAR 660 high torque control

- › Extremely powerful laboratory stirrer for highly viscous applications with a torque of up to 660 Ncm
- › For viscosities up to 150,000 mPas

The optimal stirrer for your application

OVERHEAD STIRRERS FOR LIGHT STIRRING TASKS



EUROSTAR 20 digital
Ident. No. 0020105154



EUROSTAR 40 digital
Ident. No. 0020105155



EUROSTAR 60 digital
Ident. No. 0020105156



EUROSTAR 60 control
Ident. No. 0020105158

ULTRA HIGH TORQUE
OVERHEAD STIRRERS



EUROSTAR 400
high torque digital
Ident. No. 0020105162



EUROSTAR 660
high torque control
Ident. No. 0004090000

HIGH-SPEED
OVERHEAD STIRRERS



EUROSTAR 20
high speed digital
Ident. No. 0020105160



EUROSTAR 20
high speed control
Ident. No. 0020105161

POWERFUL OVERHEAD STIRRERS
FOR UNIVERSAL STIRRING TASKS



EUROSTAR 100 digital
Ident. No. 0020105157



EUROSTAR 100 control
Ident. No. 0020105159



EUROSTAR 200 digital
Ident. No. 0003990000



EUROSTAR 200 control
Ident. No. 0003992000

PILOT SCALE OVERHEAD STIRRERS



EUROSTAR 400 digital
Ident. No. 0004214000



EUROSTAR 400 control
Ident. No. 0004214100

Technical data

Technical data	EUROSTAR 20 digital 40 digital	EUROSTAR 60 digital control	EUROSTAR 100 digital control
Stirring quantity max. (H ₂ O)	25 l	60 l	100 l
Max. viscosity	10 000 mPas 30 000 mPas	50 000 mPas	70 000 mPas
Motor rating input / output	70 / 42 W 118 / 84 W	168 / 131 W	186 / 136 W 174 / 142 W
Permissible ON time	100 %	100 %	100%
Speed range	0/30 – 2000 rpm	0/30 – 2000 rpm	0/30 – 2000 rpm
Speed range I (at 50/60 Hz)	–	–	–
Speed range II (at 50/60 Hz)	–	–	–
Max. torque at stirring shaft	40 Ncm 60 Ncm	100 Ncm	200 Ncm (120 Ncm continuous)
Display	LCD	LCD TFT	LCD TFT
Reverse operation	no	no yes	no yes
Intermittent operation	no	no yes	no yes
Temp. sensor connection	no	no PT 1000	no PT 1000
Chuck range	0.5 – 10 mm	0.5 – 10 mm	0.5 – 10 mm
Hollow shaft	yes	yes	yes
Torque trend measurement	yes	yes	yes
Timer	yes	yes	yes
Temperature measurement	no	no yes	no yes
Temperature measuring range	–	– -10 to 350 °C	– -10 to 350 °C
Dimensions (W × D × H)	89 × 191 × 237 mm	89 × 191 × 237 mm	89 × 191 × 237 mm
Weight	3.8 kg	3.8 kg 3.9 kg	3.8 kg 3.9 kg
Permissible ambient temp.	5 – 40 °C	5 – 40 °C	5 – 40 °C
Permissible relative moisture	80%	80%	80%
Protection class DIN EN 60529	IP 54	IP 54	IP 54
USB / RS 232 interface	yes	yes	yes
Voltage	230 V	230 V	230 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz

EUROSTAR 200 digital control	EUROSTAR 400 high torque digital EUROSTAR 660 high torque control	EUROSTAR 20 high speed digital control	EUROSTAR 400 digital control
100 l	100 l	20 l	150 l
100 000 mPas	100 000 mPas 150 000 mPas	10 000 mPas	100 000 mPas
130 / 84 W	174 / 142 W 134 / 76 W	176 / 125 W	220 / 176 W
100%	100%	100%	100%
0/6 – 2000 rpm	10 – 300 rpm 0/4 – 530 rpm	0/150 – 6000 rpm	0/6 – 2000 rpm
0/6 – 400 rpm	– 0/4 – 110 rpm	–	0/6 – 400 rpm
0/30 – 2000 rpm	– 0/16 – 530 rpm	–	0/30 – 2000 rpm
200 Ncm	400 Ncm 660 Ncm	20 Ncm	400 Ncm
LED TFT	TFT	LED TFT	LED TFT
no	no	no	no
no yes	yes	no yes	no yes
no PT 1000	PT 1000	no PT 1000	no PT 1000
0.5 – 10 mm	0.5 – 10 mm	fixed	0.5 – 10 mm
yes	no	no	yes
no yes	yes	no yes	no yes
no yes	yes	no yes	no yes
no yes	yes	no yes	no yes
– -10 to 350 °C	– -10 to 350 °C	– -10 to 350 °C	– -10 to 350 °C
91 × 209 × 274 mm 91 × 231 × 274 mm	86 × 352 × 230 mm 91 × 230 × 379 mm	86 × 208 × 325 mm 86 × 230 × 325 mm	114 × 245 × 300 mm 114 × 268 × 320 mm
4.6 kg 4.9 kg	5.2 kg 5.8 kg	5.3 kg 4.7 kg	7.8 kg 8.2 kg
5 – 40 °C	5 – 40 °C	5 – 40 °C	5 – 40 °C
80%	80%	80%	80%
IP 40	IP 40	IP 40	IP 40
no yes	yes	no yes	no yes
230 V	230 V	230 V	230 V
50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz

RW series

/// Stirring larger volumes

Powerful, mechanically controlled laboratory stirrers designed for highly viscous applications. The stirrers of the RW series are suitable for intensive mixing for use in laboratories and pilot plants.



RW 20 digital
Ident. No. 0003593000

The bestseller in the laboratory

- › With digital display
- › Robust, slimline, ergonomic design
- › With constant power-drive
- › Two speed ranges for universal use from 60 – 2000 rpm
- › Push-through agitator shafts (only when stationary)
- › For stirring quantities of up to 20 l (H₂O)



RW 28 digital
Ident. No. 0005040000

For quantities up to 80 l (H₂O)

- › Infinitely adjustable speed from 60 to 1400 rpm in two speed ranges



RW 47 digital
Ident. No. 0004050000

For quantities up to 200 l (H₂O)

- › Infinitely adjustable speed from 57 – 1300 rpm in two speed ranges
- › SI 400 safety switch and SI 474 fixing device are available as optional accessories allowing the user to switch on the device only at a defined height in the stand's working range

FEATURES

RW 28 digital & RW 47 digital


- › Digital speed display
- › Push-through agitator shafts
- › Overload protection
- › Error code display
- › Robust, ergonomic design
- › Quiet operation
- › With constant power-drive

Technical data

Technical data	RW 20 digital	RW 28 digital	RW 47 digital
Stirring quantity max. (H ₂ O)	20 l	80 l	200 l
Max. viscosity	10 000 mPas	50 000 mPas	100 000 mPas
Motor rating input/output	70 / 35 W	220 / 90 W	513 / 370 W
Permissible ON time	100%	100%	100%
Speed range (at 50/60 Hz)	60 – 2000 rpm / 72 – 2400 rpm	60 – 1400 rpm / 72 – 1680 rpm	57 – 1300 rpm / 69 – 1560 rpm
Speed range I (at 50/60 Hz)	60 – 500 rpm / 72 – 600 rpm	60 – 400 rpm / 72 – 480 rpm	57 – 275 rpm / 69 – 330 rpm
Speed range II (at 50/60 Hz)	240 – 2000 rpm / 288 – 2400 rpm	240 – 1400 rpm / 288 – 1680 rpm	275 – 1300 rpm / 330 – 1560 rpm
Max. torque at stirring shaft	150 Ncm	900 Ncm	3000 Ncm
Display	LED	LED	LED
Reverse operation	no	no	no
Intermittent operation	no	no	no
Temp. sensor connection	no	no	no
Chuck range	0.5 – 10 mm	1 – 10 mm	3 – 16 mm
Hollow shaft	yes	yes	no
Torque trend measurement	no	no	no
Timer	no	no	no
Temperature measurement	no	no	no
Temperature measuring range	–	–	–
Dimensions (W × D × H)	88 × 212 × 294 mm	123 × 252 × 364 mm	145 × 358 × 465 mm
Weight	3.1 kg	7.5 kg	16 kg
Permissible ambient temp.	5 – 40 °C	5 – 40 °C	5 – 40 °C
Permissible relative moisture	80%	80%	80%
Protection class DIN EN 60529	IP 20	IP 40	IP 54
USB / RS 232 interface	no	no	no
Voltage	220 – 240 V	220 – 240 V	3 × 400 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz

Accessories

Stirring elements



Product	Shaft length Shaft diameter Stirrer diameter	Max. speed	Material	Ident. No.
SCREW-TYPE STIRRERS				
R 1002	140 4 12 mm	2000 rpm	Stainless steel	0000527500
PROPELLER STIRRERS, 3-BLADED				
R 1381	350 8 45 mm	≤ 2000 rpm	Stainless steel	0001296000
R 1382	350 8 55 mm	≤ 2000 rpm	Stainless steel	0001295900
R 1385	550 10 140 mm	≤ 800 rpm	Stainless steel	0000477700
R 1388	800 10 140 mm	≤ 400 rpm	Stainless steel	0000477800
R 1389*	350 8 75 mm	≤ 800 rpm	PTFE-coated	0002343600
PROPELLER STIRRERS, 4-BLADED				
R 1342	350 8 50 mm	≤ 2000 rpm	Stainless steel	0000741000
R 1345	550 8 100 mm	≤ 800 rpm	Stainless steel	0000741300
R 2302	800 13 150 mm	≤ 600 rpm	Stainless steel	0000739000
R 1346	350 8 58 mm	≤ 800 rpm	PTFE-coated	0025006431
TURBINE STIRRERS				
R 1311	350 8 30 mm	≤ 2000 rpm	Stainless steel	0002332900
R 1312	350 8 50 mm	≤ 2000 rpm	Stainless steel	0002333000
R 1313	400 10 70 mm	≤ 800 rpm	Stainless steel	0002333100
CENTRIFUGAL STIRRERS				
R 1352	350 8 60/15 mm	≤ 2000 rpm	Stainless steel	0000756900
R 1355	550 8 100/24 mm	≤ 800 rpm	Stainless steel	0001132700
MOEBIUS STIRRERS				
R 3000.1	565 10 100 mm	≤ 800 rpm	Stainless steel	0020001192
R 3001.1	575 10 100 mm	≤ 800 rpm	Stainless steel	0020001195
SPIRAL STIRRERS				
R 3003	350 8 50 mm	≤ 800 rpm	Stainless steel	0020001203
R 3003.1	550 10 100 mm	≤ 800 rpm	Stainless steel	0020001204
R 3003.2	800 10 150 mm	≤ 800 rpm	Stainless steel	0020001205



* (PTFE-coated)

NANO-STAR 7.5 digital	MICRO-STARS digital control	MINI-STARS digital control	EUROSTAR 20 40 digital	EUROSTAR 60 digital control	EUROSTAR 100 digital control	EUROSTAR 200 digital control	EUROSTAR 400 digital control	EUROSTAR 100 & 200 control P4	RW 20 digital	RW 28 digital	RW 47 digital
++	++	++	++	+	+	+	+	+	++	+	+
++	++	++	++	++	++	+	+	+	++	+	+
++	++	++	++	++	++	+	+	+	++	+	+
-	-	-	+	++	++	++	++	++	+	++	++
-	-	-	+	+	++	++	++	++	+	++	++
++	++	++	++	++	++	++	++	++	++	++	+
++	++	++	++	++	++	+	+	+	++	+	+
+	+	+	+	++	++	++	++	++	++	++	++
-	-	-	-	-	-	-	++	-	-	-	++
++	++	++	++	++	++	++	++	++	++	++	++
++	++	++	++	++	++	+	+	+	++	+	+
++	++	++	++	++	++	+	+	+	++	+	+
-	-	-	+	++	++	++	++	++	+	++	-
++	++	++	++	++	++	+	+	+	++	+	+
++	++	++	++	++	++	++	++	++	++	++	++
+	+	+	+	++	++	++	++	++	++	++	++
-	-	-	++	++	++	++	++	++	++	++	++
-	-	-	++	++	++	++	++	++	++	++	++
+	+	+	++	++	++	++	++	++	++	++	++
-	-	-	++	++	++	++	++	++	++	++	++
-	-	-	-	-	+	+	++	-	-	++	++

++ IKA recommended | + Installable | - Not compatible

Accessories

Stirring elements



Product	Shaft length Shaft diameter Stirrer diameter	Max. speed	Material	Ident. No.
---------	--	------------	----------	------------

DISSOLVER STIRRERS

R 1300	350 8 80 mm	≤ 2000 rpm	Stainless steel	0000513500
R 1302	350 10 100 mm	≤ 1000 rpm	Stainless steel	0002387900
R 1303	350 8 40 mm	≤ 2000 rpm	Stainless steel	0002746700

BLADE STIRRERS

R 3004	359 8 30 mm	≤ 1000 rpm	Stainless steel	0020001206
R 3004.1	565 10 50 mm	≤ 1000 rpm	Stainless steel	0020001207
R 3004.2	819 10 70 mm	≤ 1000 rpm	Stainless steel	0020001208

CUP STIRRERS

R 3005	500 10 80 mm	≤ 1000 rpm	Stainless steel	0020122341
--------	------------------	------------	-----------------	------------

PADDLE STIRRERS

R 1001	160 4 34 mm	2000 rpm	Stainless steel	0000527400
R 1375	550 8 70 mm	≤ 800 rpm	Stainless steel	0000757700
R 1376	550 10 150 mm	≤ 800 rpm	Stainless steel	0000757800
R 2311	800 13 150 mm	≤ 600 rpm	Stainless steel	0000739500

ANCHOR STIRRERS

R 1330	350 8 45 mm	≤ 1000 rpm	Stainless steel	0002022300
R 1331	350 8 90 mm	≤ 1000 rpm	Stainless steel	0002022400
R 1333	550 10 150 mm	≤ 800 rpm	Stainless steel	0002747400
RS 1330	350 8 90 mm	≤ 800 rpm	Stainless steel	0010015122
RS 1331	350 8 150 mm	≤ 800 rpm	Stainless steel	0010015123
RS 1333	550 10 220 mm	≤ 800 rpm	Stainless steel	0010015124

* (PTFE-coated)

NANO-STAR 7.5 digital	MICRO-STARS digital control	MINI-STARS digital control	EUROSTAR 20 40 digital	EUROSTAR 60 digital control	EUROSTAR 100 digital control	EUROSTAR 200 digital control	EUROSTAR 400 digital control	EUROSTAR 400 660 high torque	RW 20 digital	RW 28 digital	RW 47 digital
-----------------------	-------------------------------	------------------------------	--------------------------	-------------------------------	--------------------------------	--------------------------------	--------------------------------	--------------------------------	---------------	---------------	---------------

++	++	++	++	++	++	++	++	++	++	++	+
-	-	-	+	++	++	++	++	++	+	++	++
++	++	++	++	++	++	+	+	+	++	+	+




++	++	++	++	++	++	+	+	+	++	+	+
-	-	-	++	++	++	+	+	+	++	+	+
-	-	-	++	++	++	++	++	++	++	++	++

-	-	-	++	++	++	++	+	++	++	+	+
---	---	---	----	----	----	----	---	----	----	---	---


++	++	++	++	+	+	+	+	+	++	+	+
+	+	+	+	++	++	++	++	++	+	++	+
-	-	-	+	+	+	++	++	++	+	++	++
-	-	-	-	-	-	-	++	-	-	-	++

++	++	++	++	++	++	++	+	++	++	+	+
+	+	+	+	++	++	++	++	++	-	++	-
-	-	-	+	+	+	++	++	++	+	++	++
++	++	++	++	++	++	++	+	++	++	+	+
+	+	+	+	++	++	++	++	++	-	++	-
-	-	-	+	+	+	++	++	++	+	++	++

++ IKA recommended | + Installable | - Not compatible




STIRRER	SCREW-TYPE	PROPELLER 3-BLADED	PROPELLER 4-BLADED
Image			
Flow direction (Diagram)			
Tip speed / circumferential speed (m/s)	0.01 – 1.3	2 – 15	2 – 15
Direction	AXIAL	AXIAL	AXIAL
Mixing speed	Medium – high	Medium – high	Medium – high
Shear forces	Low	Medium	Medium
Viscosity	Low	Low – medium	Low – medium
Applications	Narrow stirrer for use in small scale applications and vials.	Flow-efficient design to provide up and bottom flow pattern while creating minimum shearing forces.	Standard stirring element for general mixing applications. It creates local shearing forces and axial flow in the vessel.
Preferred geom. dimension d_2/d_1	0.2 – 0.5	0.1 – 0.5	0.2 – 0.5
Preferred geom. dimension h_2/d_1	0.3 – 3	0.3 – 3	0.3 – 3
Preferred geom. dimension h_1/d_1	1.0	1.0	1.0




d_1 : container diameter
 d_2 : stirrer diameter
 h_1 : fill height
 h_3 : bottom distance




Mixing Range	Speed
Low	< 150 rpm
Medium	150 to 800 rpm
High	> 800 rpm

Viscosity Range	mPas	Example (at 20 °C)
Low	< 1000	Water to motor oil
Medium	< 10 000	Honey
High	> 10 000	Asphalt

TURBINE	CENTRIFUGAL	MOEBIUS
		
		
2 – 15	2 – 15	2 – 10
AXIAL	AXIAL	AXIAL
Medium – high	Medium – high	Medium
Low	Low	Very low
Low	Low	Low – medium
This stirrer is used for drawing the material to be mixed from above within the vessel. It carries a minimum level of danger of injury when contact is made with sensor or vessel.	Two-bladed stirrer whose blades open with increasing speed. Perfect for stirring in round vessels with narrow necks and the effect is similar to that of a 4-bladed propeller stirrer.	Drawing the material to be mixed from the top and the bottom while creating minimum shearing forces.
0.2 – 0.5	0.2 – 0.5	0.2 – 0.5
0.3 – 3	0.3 – 3	0.3 – 3
1.0	1.0	1.0




STIRRER	SPIRAL	DISSOLVER	BLADE
Image			
Flow direction (Diagram)			
Tip speed / circumferential speed (m/s)	2	8 – 20	3 – 7
Direction	AXIAL	RADIAL	RADIAL
Mixing speed	Low – medium	Medium – high	Medium – high
Shear forces	low	Very High	High
Viscosity	Medium – high	Low	Low – medium
Applications	Medium is conveyed from the bottom upwards. For homogeneous mixing and heat exchange of medium.	This stirrer provides drawing the material to be mixed from the top and the bottom while creating high turbulence and high shearing forces for particle reduction or break down agglomeration.	This stirrer draws the material to be mixed from the top and the bottom while creating high turbulence and high shearing forces for dispersion or gassing of liquid.
Preferred geom. dimension d_2/d_1	0.9 – 0.98	0.2 – 0.5	0.2 – 0.5
Preferred geom. dimension h_2/d_1	–	0.3 – 3	0.3 – 3
Preferred geom. dimension h_1/d_1	1.0	1.0	1.0

d_1 : container diameter
 d_2 : stirrer diameter
 h_1 : fill height
 h_2 : bottom distance



Mixing Range	Speed
Low	< 150 rpm
Medium	150 to 800 rpm
High	> 800 rpm

Viscosity Range	mPas	Example (at 20 °C)
Low	< 1000	Water to motor oil
Medium	< 10 000	Honey
High	> 10 000	Asphalt

CUP	ANCHOR	PADDLE
		
		
2 – 8	1 – 5	1 – 3
RADIAL	TANGENTIAL	TANGENTIAL
Low – medium	Low	Low – medium
Medium	Low	Low
Low – medium	High	Medium – high
This stirrer uses conical impeller shape for dynamic mixing movements, and ensures circulation without dead spaces or vortex formation while minimizing foaming.	This stirrer creates tangential flow, high shearing rate at the edges, minimum deposits on the vessel wall making them great for polymer reactions and even distribution of high mineral contents in liquids.	This stirrer creates tangential flow, minimum turbulence, good heat exchange, and gentle treatment of the product.
0.2 – 0.5	0.9 – 0.98	0.5 – 0.7
0.3 – 3	–	–
1.0	1.0	0.75

Accessories



BC 1000 Beaker cap
Can be used with 1000 ml and 600 ml beakers for dispersing and stirring experiments.
[Ident. No. 0020003417](#)



FK 1 Flexible coupling
Required for stirring tasks using glass stirring rods. The flexible coupling compensates for any structural variances.
[Ident. No. 0002336000](#)



RH 3 Strap clamp
For securing vessels during stirring.
[Ident. No. 0003008600](#)




RH 5 Strap clamp
For securing vessels against walls or for synchronized rotation during stirring, incl. boss head clamp R 270.
[Ident. No. 0003159000](#)

R 6547 H Floor stand
Manually adjustable, extendable floor stand, for RW 47 digital and T 65 basic/digital.
[Ident. No. 0020018378](#)


R 2850 Floor stand
Mobile floor stand, with H-shape base which prevents against tipping. For overhead stirrers and dispersers with a diameter of extension arm of 13 – 16 mm.
[Ident. No. 0020002900](#)

Plate stands
R 1825 / R 1826 / R 1827
With slip resistant foil.
[Ident. No. 0003160000](#)
[Ident. No. 0003160100](#)
[Ident. No. 0003160200](#)


IKA [scale] Weighing stand
A stand with an integrated scale and data interface: only available from IKA.
[Ident. No. 0025004318](#)




Height: 1635 mm



Height: 1900 mm



Height R 1825: 560 mm
R 1826: 800 mm
R 1827: 1000 mm



Height: 570 mm



Height: 1010 mm



Height: 620 – 1010 mm
Stroke: 390 mm



Height: 1200 mm
Stroke: 500 – 1000 mm



Height: 2020 mm
Stroke: 980 – 1860 mm



NANOSTAR



MICROSTAR
digital | control



MINISTAR
digital | control



EUROSTAR 20 | 40
digital



EUROSTAR 60
digital | control



EUROSTAR 100
digital | control



EUROSTAR 200
digital | control



EUROSTAR 400
digital | control



EUROSTAR 400 high torque digital |
EUROSTAR 660 high torque control



EUROSTAR 20 high speed
digital | control



RW 20
digital



RW 28
digital



RW 47
digital

* IKA recommendations only

Accessories for RW 47 digital



R 303
Stirring shaft protection for RW 47 digital.
Ident. No. 0030000257



SI 400
Safety switch
Ident. No. 0003294800



SI 472
Fixing device for R 472 stand.
Ident. No. 0003264000



SI 474
Fixing device for R 474 and T 653 stand.
Ident. No. 0003264400

Accessories for RW 20 digital & EUROSTAR series



R 60 Keyless chuck
Only for use with EUROSTAR 20 / 40 / 60 / 100 / 200 / RW 20, excluding EUROSTAR 20 high speed digital and control.
Clamping range: 0.5 – 10 mm
Ident. No. 0003889500



R 60.1 Keyless chuck
Compatible with MINISTAR 20 / 40 / 80 digital and control, MICROSTAR series and NANOSTAR 7.5 digital.
Clamping range: 0.5 – 8 mm
Ident. No. 0025007821



R 401 Stirring shaft protection with hinge
Ident. No. 0020122349

R 402 Stirring shaft protection
Ident. No. 0020115312



R 301.1 Support holder
For fixing the stirring shaft protection R 301 to the stand when in use with overhead stirrers NANOSTAR 7.5 digital, MINISTAR, MICROSTAR series and EUROSTAR 400.
Ident. No. 0002604000



H 67.60
Temperature sensor made of stainless steel.
Ident. No. 0025006664



H 67.61
Temperature sensor made of stainless steel with a fast response time.
Ident. No. 0025007920



H 66.51 Temperature sensor
Temperature sensor, stainless steel, glass-coated, Ø 6 mm, 260 mm length.
Ident. No. 0002735551



H 66.53 Temperature sensor
Chemical resistant coated sensor, extension cable H 70 required for connection.
Ident. No. 0004499900



H 70 Extension cable
To connect EUROSTAR control with the temperature sensor.
Ident. No. 0002735600





WH 11
Wall mount for wireless controller (WiCo)
Ident. No. 0025001500



labworldsoft® 6 Starter | Pro | Advanced
labworldsoft® is a multi-purpose software program for measuring, controlling and regulating laboratory devices.
Ident. No. 0020019397 | 0020017366 | 0020105873



IQ/OQ Documentation LAB
Ident. No. 0010006581




- | | | | | | |
|-------------------------------|-----------------------|-----------------------------|--------------------------------------|-----------------------------|------------------------------------|
| NANOSTAR 7.5 digital | MICROSTAR 7.5 control | MICROSTAR 15 digital | MICROSTAR 15 control | MICROSTAR 30 digital | MICROSTAR 30 control |
| MINISTAR 20 digital / control | MINISTAR 40 digital | MINISTAR 40 control | MINISTAR 80 digital | MINISTAR 80 control | |
| ES 200 control P4 I | ES 40 digital | ES 100 digital / control | ES 60 digital / control | ES 20 digital | ES 20 high speed digital / control |
| ES 200 digital / control I | ES 200 control P4 II | ES 200 digital / control II | ES 400 digital / control I | ES 400 digital / control II | ES 100 control P4 |
| RW 47 digital | RW 28a digital | RW 20 digital | I : speed step 1
II: speed step 2 | | |

Constant torque over the entire speed range

High torque at low speed and the torque decreases when the speed increases.

Speed range I is for highly viscous samples and speed range II is for intensive mixing of low viscous samples.



Quality standards



DIN EN IEC 61010-1
DIN EN IEC 61010-2-051



Integrated Safety
All IKA overhead stirrers adhere to the requirements set forth by the norms DIN EN IEC 61010-1 and DIN EN IEC 61010-2-051.

They meet and exceed CE standards and fulfill international safety regulations.

Knowledge

Torque

Torque is mathematically defined as the vector product of force and lever arm. It is therefore calculated as $M = F \cdot r$, where M is the torque, r is the lever arm and F is the force. The magnitude of the force is based on the perpendicular distance from the axis of rotation to the line of action of the force.

Typical dynamic viscosity values
(Range 1 – 100 000 mPa*s)

Substance	Viscosity η in mPa*s
Water	1
Milk	2
Coffee whipped cream	10
Olive oil	100
Lubricant oil	200
Motor oil	650 – 900
Shampoo	3000
Hand cream	8000
Honey	10 000
Ketchup	50 000
Toothpaste (40 °C)	70 000
Asphalt	100 000

Unless otherwise stated, the values refer to the viscosity at 20 °C and atmospheric pressure

The unit of measurement of torque is Nm. For example, in mixing systems, the drive power of an electric motor is delivered to the rotating drive shaft or the drill chuck fixed to the mixing tool. What matters is the transfer of power in the drive to the rotating mixing tool. Torque is the key to the relationship between the mixing tool geometry, viscosity of the medium to be mixed and the speed of rotation. The power is transferred from the motor to the shaft and then to the mixing tool. The torque acts on the mixing tool at the drill chuck as shown in the brochure.

Viscosity

The “viscosity” shown in our brochure always refers to the dynamic viscosity η . Viscosity is a measure of the fluid’s resistance to flow or change in shape due to internal friction between the molecules. If a fluid has high viscosity, then it strongly resists flow. This is an important parameter to be considered when it is required to create product emulsions and suspensions by mixing and homogenizing or merely in the transfer of fluids from one location to another.

$1N = [\eta] \cdot (m^2\ m / m\ s) \Rightarrow [\eta] = Ns / m^2 = Pa*s$

Fluids are either Newtonian or Non-Newtonian. Fluids whose viscosity is constant at all shear rates are called Newtonian fluids (e.g., pure fluids, ideal fluids / water, oil and most gases which have a constant viscosity). Fluids whose viscosity is not constant at all shear rates are called Non-Newtonian fluids (e.g., blood, sand-water mixtures, dough, puddings, asphalt cement, etc.).

Oil is a good example of a highly viscous liquid. It does not flow easily and affects parameters such as the thickness of the lubricating film in bearings, motors, gear units, leakage losses in the hydraulics, pump efficiency and friction losses in pipes.

Applications and Industries

- Food:** Butter, mayonnaise, ketchup...
- Cosmetics:** Creams, shampoo, soap...
- Pharmaceutical and chemical industry:** Pills, suppositories, aluminium oxide, glycerin...
- Abrasives:** Silicon carbide, crystals, sand...
- Inks, coatings, paints and pigments:** printing ink, metallic paints, color pigment suspension...
- Glues and adhesives:** Adhesive mixture, Vaseline, two-component glue...
- Plastics and polymers:** PVC powder, pre-polymer, polyester resin...
- Cement and construction:** Concrete, mineral clay, loam...

FAQ

1. Does IKA supply an explosion-proof stirrer system?

IKA does supply custom-made explosion-proof systems for larger volumes upon request.

2. What does torque trend display mean in the case of the new EUROSTAR range – can they measure viscosity?

The EUROSTAR digital units only display the change in torque. Normally, this is associated with a change in the viscosity of the medium. The EUROSTAR control units can directly use the torque sensor to calculate from the data the product viscosity.

3. How long can a stirrer be operated without interruption?

All IKA stirrers have a 100% duty cycle, i.e. they can be operated without interruption.

4. Are there any stirrers which rotate in different directions?

All IKA stirrers rotate in clockwise direction except for EUROSTAR 60 control, EUROSTAR 100 control and EUROSTAR 400 high torque digital which rotates in both clockwise and counter clockwise direction. Additionally, upon request for special applications, counter clockwise direction can be incorporated.

5. What is the difference between the electronic and mechanical versions of the stirrers?

In mechanical stirrers, the speed is set by means of a continuously variable transmission. A higher torque can be made available directly in the lower speed range by altering the transmission ratio of the actuator. Whereas in electronic stirrers, the power output is monitored and controlled by a processor. This ensures a constant speed range even with changes in viscosity.

6. What quantities and viscosities can be processed with IKA stirrers?

Depending on the unit, maximum stirring quantity ranges from 20 ml to 200 liters. Similarly, the viscosity ranges from 1 mPas to 150 000 mPas.

7. What should be the diameter of the vessel in relation to the stirrer tool?

In the case of water, the diameter of the vessel should be twice the diameter of the stirrer element and the height two or three times that of the stirrer element. In case of high viscosity material, the stirrer element should be closer to the vessel wall.

8. What ambient conditions are required for the operation of IKA stirrers?

The ambient temperature should be consistent between 5 °C and 40 °C and the humidity should not exceed 80%.





designed for scientists

Everything for your Lab

IKA is your reliable partner in laboratory, analysis and process technology. When it comes to applications in the areas of stirring, mixing, tempering, distilling or grinding, market leaders rely on our proven products and technology. We are continually working to further develop our portfolio according to the needs of our customers. Building on this, we network our products and services to create holistic, application-oriented solutions and enable our customers to achieve the best possible results and step into the digital age.



BIOREACTORS



MIXING



HEATING / COOLING /
TEMPERING



LIQUID HANDLING



MEASURING VISCOSITY



VACUUM TECHNOLOGY



CRUSHING



LABORATORY SOFTWARE



SEPARATION



ELECTROCHEMISTRY



REACTOR SYSTEMS



CALORIMETRY

IKA-Werke GmbH & Co. KG
Janke & Kunkel-Straße 10,
79219 Staufen, Deutschland
+49 7633 831-0 / sales@ika.de



IKAworlwide // #lookattheblue



Stay up to date:
[www.ika.com/
newsletter](http://www.ika.com/newsletter)

Technical specifications are subject to
change without notice.
Information on delivery not binding